Touch Panel Monitors
- Accessories
- Model Comparison
- Ecology & Ergonomics

Downloads
- ICC Profiles
- Software
- Brochures
- Manuals

Support
- FAQs
- Compatibility
- Warranty
- Glossary
- Discontinued Models

FlexScan T1502
FlexScan T1501

Specifications

Panel	Panel Size and Type		38 cm (15") TFT color LCD panel
	Viewing Angles (H, V)		160°, 150°(at contrast ratio of 5:1)
	Brightness / Contrast		195 cd/m² / 700:1
	On/Off Response Time		8 ms (typical)
	Native Resolution		1024 × 768
	Active Display Size (H × V)		304 × 228 mm
	Viewable Image Size		Diagonal: 380 mm
	Pixel Pitch		0.297 × 0.297 mm
	Display Colors		16.19 million (maximum)
Cabinet Colors			Gray, Black
Dot Clock			Analog: 80 MHz, Digital: 65 MHz
Scanning Frequency (H, V)		Analog	24.8 – 60 kHz, 55 – 75 kHz
		Digital	31 – 49 Hz, 59 – 61 Hz (VGA Text: 69 – 71 Hz)
Input Signals			Analog: RGB Analog, Digital: DVI Standard 1.0
Input Terminals			D-Sub mini 15 pin, DVI-D 24 pin (switchable)
Plug & Play			VESA DDC 2B
Power	Power Requirements		AC 100 – 120 V, 200 – 240 V: 50 / 60 Hz
	Power Consumption		25 W (maximum)
	Power Save Mode		Less than 1 W
Physical Specifications	Tilt / Swivel / Pivot		30° Up, 0° Down / 35° Right , 35° Left / –
	Dimensions (W ×H × D)		With Stand: 346 × 379.5 × 175 mm 13.6 × 14.9 × 6.9" Without Stand: 346 × 280 × 69 mm 13.6 × 11.0 × 2.72c
	Net Weight		With Stand: 6.1 kg / 13.5 lbs Without Stand: 4.1 kg / 9.1 lbs
Auto Brightness Functions			BrightRegulator
Auto Adjustment Functions (analog only)			Auto Adjustment
Display Mode Options			Text, sRGB, Custom
ScreenManager OSD Adjustment Functions	Screen Adjustment		Clock, Phase, Position, Range Adjustment (Auto/RGB), Smoothing (5 stages)
	Color Adjustment		Brightness, Contrast, Gamma, Temperature (14 stages: in 500 K increments from 4000 K – 10000 K including 9300 K), Saturation, Gain, Reset
	Power Save Settings	Analog	VESA DPMS
		Digital	DVI DMPM
	Sound		Volume
			Signal Switching, Power Indicator, Product Information (product name, serial number,

Other Functions	operating time), OSD Menu Position, BrightRegulator, Adjustment Lock, Languages (English, German, French, Italian, Japanese, Simplified Chinese, Spanish, Swedish, Traditional Chinese), Off Timer, Reset
Audio1	Dual 0.5 W built-in speakers, input/headphone jacks
Certifications and Standards	TÜV/GS, C-Tick, CE, CB, UL (cTÜVus), CSA (cTÜVus), FCC-B, Canadian ICES-003-B, TÜV/S, VCCI-B, RoHS, WEEE, CCC, EIZO Eco Products 2006
Supplied Accessories	AC power cord, user's manual, signal cable (D-Sub mini 15 pin – D-Sub mini 15 pin), touch panel cable (T1502 / USB, T1501 / RS-232C), audio cable. quick reference, CD-ROM (touch panel driver and user's manual), 4 screws for mount option, warranty card
Warranty	Three Years

Touch Panel

Touch Panel Type	Analog resistive
Optical Clarity	80%
Touch Life	10 million touches (minimum)
Compatible OS	Windows 2000 / XP
Communication Protocol	T1502: USB, T1501: RS-232C serial